

Tel: +44 (0) 1489 776000

info@bainbridgeint.co.uk · www.bainbridgeint.com

## **DATA SHEET**

## K750 - 1000hr UV Super Clear 0.50mm PVC Window Material

Clear vinyl formulated with UV inhibitors for use in marine canvas, tents, enclosures, soft-sided windows and many other applications. Featuring high transparency, no obvious "water ripple" phenomenon and low shrinkage, this product is suitable for high frequency welding and is also fire retardant.

Technical Detail	Test	Typical Value	Unit
Material	-	PVC	-
Colour	-	Transparent	-
Finish	-	Glossy	-
Thickness	ASTM D1593	0.50	mm
Thickness	ASTM D 751	20	mil
Roll Width	-	1500	mm
Roll Length	-	30	m
Softness	-	44	PHR
Hardness	ASTM D2240	89	Shore A
Fire Resistance	-	B1, B2, NFPA-701	-
Temperature Resistance	ASTM D1790A-94	-20 to +50	°C

All Bainbridge International products are subjected to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. The information contained in this specification is based on our current experience, values given are for guidance purpose only. Bainbridge International reserve themselves the right to proceed to any modification to improve the quality to their products. Published information concerning Bainbridge International products is based upon research, which the Company believes to be reliable. but some information does not constitute a warranty. Because of the variety of possible uses for Bainbridge International products and continuing development of new uses, the purchaser should carefully consider the fitness and performance of the product for each intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential damages. All specifications are subject to change without prior notice.

