

SOLIDS & STRIPES

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella solution dyed acrylic		
Weave	Canvas		ISO 7211-1
Finish	Water-repellent & Stain-proof		
Weight	260	g/m ²	ISO 3801
Width	137	cm	EN 1773
Roll length	50	ml	

FABRIC RESISTANCE

Oil-resistant properties	5		class /8	ISO 14419
Spray test	5		class /5	ISO 4920
Schmerber	200		mm	ISO 811
Stability on washing (40 °C)	+/-1	+/-1	%	ISO 5077
Stitching strength	42.9	51.1	daN	ISO 13935-2
Seam slippage resistance (180 N)	<3	<3	mm	ISO 13936-2
Tensile strength	160	90	daN/5cm	ISO 13934-1
Elongation at break	33	26	%	ISO 13934-1

COLOUR-FASTNESS

Colour fastness UV - indoor	8		class /8	ISO 105 B02
Colour fastness UV - outdoor - 1000h	4-5		class /5	ISO 105 B04
Colour fastness under dry friction	5		class /5	ISO 105X12
Colour fastness under wet friction	5		class /5	ISO 105X12
Colour fastness 40°C washing	5		class /5	ISO 105 C06

USES

Guarantee	5	years	
Recommended use	Cushions, Curtains, Seating, Parasol, Roman blinds, Pergola, Sail shade		

CARE



Ironing reinforces the treatment

This product's values may vary with a tolerance of $\pm 5\%$

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK

