

SUNBRELLA PLUS

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella® acrylic			
Finish	Resin based anti-fongi coating, water and UV resistant			
Weave	Canvas			ISO 7211-1
Weight	320		g/m ²	ISO 3801
Width	152		cm	EN 1773
Roll length	50		m	

FABRIC RESISTANCE

Tear strength	3.3	2.5	daN	ISO 13937-1
Oil-resistant properties	5		class /8	ISO 14419
Tensile strength	140	130	daN/5cm	ISO 13934-1
Elongation at break	30	15	%	ISO 13934-1
Schmerber	1000		mm	ISO 811
Spray test	4		class /5	ISO 4920
Air permeability	2.5		l/m ² /s	ISO 9237

COLOUR-FASTNESS

Colour fastness UV - indoor	7-8		class /8	ISO 105 B02
Colour fastness UV - outdoor - 1000h	4-5		class /5	ISO 105 B04
Colour fastness under dry friction	5		class /5	ISO 105X12
Colour fastness under wet friction	5		class /5	ISO 105X12

USES

Guarantee	5	years	
Recommended use	Sprayhood, Rear enclosure, Bimini top, Cockpit enclosure, Windscreen cover, Dodger, Console cover, Lazybag		



This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK