

Leading Brands
Responsive Solutions.

TEXTILENE
SUNSURE[®] plus
BRAND FABRIC
Synthetic Fabric

Technical Data

Item Number: T88AQS

Product Description: Awning fabric using .018" diameter vinyl-coated 500 denier polyester core yarns in the warp and the fill.

Attribute	ASTM	Warp	Fill	Typical
Construction, end/inch	D3775	36.0 + .5	15.0 + .5	
Weight, oz/yd ²	D3776	—	—	14.3
Tensile Strength (Grab), lbf	D5034	509.6	224.3	
Tensile Strength (Strip), lbf	D5035	291.9	136.9	
Tear Strength (Trapezoidal), lbf	D5587	62.0	25.5	
Elongation, %	D5035	23.5	20.8	
Abrasion Resistance (CS10/500 cycles/ with no added weight)	D3884	No exposure of core yarn		
Flammability Rating	CA Title 19 & NFPA 701-2004			
Weatherability, 1200 hours	G53-96	Trace discoloration		
Mildew Resistance	G21-96	No growth		

The above results are representative of real data from single test samples. Presently no specification is incorporated.

Suggested Applications Include:

Outdoor Furniture
Mail Carts
Barrier Netting and Fencing
Automotive Insect Screen
Pet Screen and Pet Beds
Hammocks
Bags

Strollers
Erosion Control
Commercial Laundry Carts
Youth Cots
Playground Netting
Caps and Hats