
CLICK HERE

To view stock levels and colours on our product pages

Solacryl

marine cover fabric by Bainbridge



Solacryl - PU Coated



Solacryl PU Coated Acrylic Canvas

- Biminis, tonneaus, spray hoods, flybridge and mooring covers
- Superior waterproofing giving a water column in excess of 1000mm
- Coated on one side with hi tech resin impregnation and **Infinity Process**
- Antimicrobial treatment prevents micro-organisms adhering to fabric
- Acrylic yarns give excellent UV protection



- 100% solution dyed for consistent, rich, non-fade colours
- Anti fungal coatings
- Rot proof, oil and grease resistant

INFINITY PROCESS

Solacryl Acrylic Canvas is treated with a special technological **Infinity Process** to ensure the lasting quality of the fabric. In this process, nanoparticles completely cover the surface of the fibres in the fabric, forming a permanent coat. After treatment, both the surface and the inside of the fabric are permanently protected against dirt build-up, and adverse effects of a wide variety of atmospheric agents. The low reactivity and high stability of the treatment endows long-term protection to the awning, especially against mildew and provides excellent water and oil repellence whilst allowing for superior cover shapes.

CARE & CLEANING

Proper care and cleaning should be taken to ensure the life of Solacryl Acrylic Canvas.

For regular care and maintenance, the excess dirt should be brushed from the fabric using a soft brush; the fabric should then be sprayed with warm water (not exceeding 40°C) and air-dried.

Periodically, the fabric should undergo a more thorough cleaning. Again, brush fabric with a soft bristled brush, spray with warm water, then apply a gentle soap. Let stand for 10 to 20 minutes taking care not to let it dry, then rinse thoroughly and airdry. Do not use detergents and / or solvents.

Acrylic Canvas Technical Information

UNCOATED	
Width:	152 cm
Finish:	Flurocarbon Finishing
Water Column:	≥300 mm
Weight:	300 g/m ²
Tensile Strength:	Warp - 135 daN/5 cm Weft - 80 daN/5 cm
Water Repellence:	≥5
Oil Repellence:	≥5

PU COATED	
Width:	152 cm
Finish:	Acrylic resin coating on one side. Special finish "Infinity" anti-stain, rot proof and water resistant
Water Column:	≥1000 mm
Weight:	325 g/m²
Tensile Strength:	Warp - 155 daN/5 cm Weft - 90 daN/5 cm
Water Repellence:	≥4
Oil Repellence:	≥4

WARRANTY

Solacryl Acrylic Canvas is manufactured with only the highest quality raw materials and the most rigorous quality-assurance procedures, we offer a 5-year warranty on our 100% solution dyed acrylic products.

The warranty protects against the loss of characteristics, rot and discolouration typical in normal atmospheric conditions. This warranty does not apply against deterioration of any kind due to abusive use, accidental burns, negligence, vandalism, perforations, natural disasters or acts of nature. Normal wear, weather soiling or stains from environmental pollution or other sources are not covered.

The product must be properly installed and maintained. The warranty, if applicable, does not cover labour, frames, systems and installation supplied by the dealer.





Bainbridge International Ltd

8 Flanders Park, Southampton, Hampshire SO30 2FZ UK

T: +44 (0) 1489 776010 E: info@bainbridgeint.co.uk W: bainbridgeint.com