

# SUNBRELLA

## Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

### GENERAL CHARACTERISTICS

Composition	100% Sunbrella® acrylic		
Finish	Special marine treatment		
Weave	Canvas		ISO 7211-1
Weight	300		g/m <sup>2</sup> ISO 3801
Width	152		cm EN 1773
Roll length	50		m

### FABRIC RESISTANCE

Tear strength	3	2.5	daN	ISO 13937-1
Oil-resistant properties	5		class /8	ISO 14419
Tensile strength	140	90	daN/5cm	ISO 13934-1
Elongation at break	34	30	%	ISO 13934-1
Schmerber	400		mm	ISO 811
Spray test	4		class /5	ISO 4920
Air permeability	31.62		l/m <sup>2</sup> /s	ISO 9237

### COLOUR-FASTNESS

Colour fastness UV - indoor	7-8		class /8	ISO 105 B02
Colour fastness UV - outdoor - 1000h	4-5		class /5	ISO 105 B04
Colour fastness under dry friction	5		class /5	ISO 105X12
Colour fastness under wet friction	5		class /5	ISO 105X12

### USES

Guarantee	10	years	
Recommended use	Sprayhood, Rear enclosure, Bimini top, Cockpit enclosure, UV band, Windscreen cover, Dodger, Console cover, Lazybag		

*This product's values may vary with a tolerance of ± 5%*

**Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration**

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - [www.dickson-constant.com/en/UK](http://www.dickson-constant.com/en/UK)

