

# Window Material

## Calendered - Rolls

- UV stabilised vinyl.
- Available only on full rolls.

Part No.	Thickness: mm/in		Roll Width: mm/in		Roll Length: m/yd	
E204	0.4	0.016	1370	54	40	43.7
E206	0.5	0.020	1370	54	40	43.7
E205	0.7	0.028	1370	54	30	32.8



## 1000 hour UV Roll-A-Glass

- Passes 1000 hour UV weatherometer!
- Sparkling clarity, extended UV life window material.
- -10°F cold crack.
- USA standard: FR302 Fire resistant.



Part No.	Thickness: mm/in		Roll Width: mm/in		Roll Length: m/yd	
K631	0.50	0.02	1370	54	27	30

## Glass Clear - Window Material

Clear PVC window material used in sprayhoods, biminis and cockpit covers. Available in sheet format. Extremely scratch resistant.



Part No.	Thickness: mm/in		Sheet Width: mm/in		Sheet Length: mm/in		Pack Qty
E203	1.0	0.04	1250	49.2	2500	98.4	Each

## Strataglass - Scratch Resistant Glass

- Leading scratch resistant clear vinyl.
- Tested to 12 years accelerated UV.
- Easy roll-up, the same as regular vinyl.
- UV Blocking.
- Use: boat curtains, automotive windows, tent & awning applications.

**STRATAGLASS**




Canvas Designers Inc, FL

## Strataglass - Clear

Part No.	Gauge Thickness: mm/in		Width: mm/in		Sheet Length: mm/in		Sheets Per Drum
K305/2	0.76	0.030	1370	54	2820	111	2
K305/5	0.76	0.030	1370	54	2820	111	5
K310/2	1.02	0.040	1370	54	2820	111	2
K310/5	1.02	0.040	1370	54	2820	111	5
K315/2	1.50	0.060	1370	54	2820	111	2

## Strataglass - Smoke Tint

Part No.	Gauge Thickness: mm/in		Width: mm/in		Sheet Length: mm/in		Sheets Per Drum
 K310/2SM	1.02	0.040	1370	54	2820	111	2
K310/5SM	1.02	0.040	1370	54	2820	111	5

## Strataglass - Light Smoke Tint

Part No.	Gauge Thickness: mm/in		Width: mm/in		Sheet Length: mm/in		Sheets Per Drum
K315/2LSM	1.02	0.040	1370	54	2820	111	5

## Regalite® Flex Pressed Polished Window Material

- Best quality glass-clear PVC material.
- Regalite® is a registered trademark of Regalite Plastics Corporation, O'Sullivan Corporation.
- Available in sheet format.



Part No.	Gauge Thickness: mm/in		Sheet Width: mm/in		Sheet Length: mm/in		Qty per Drum
K221	0.50	0.020	740	29	1730	68	60
K222/5	0.76	0.030	1370	54	2270	109	60
K225/5	1.02	0.040	1370	54	2270	109	60

## Crystal Clear Vinyl Sheets

- Clear vinyl sheets.


Part No.	Gauge Thickness: mm/in		Sheet Width: mm/in		Sheet Length: mm/in		Qty
K120/10	0.50	0.020	1370	54	2820	111	1

## CLEAR-VU High Optical Clarity Roll Glass

Clear-VU is a top quality extruded vinyl product that offers optical clarity approaching the best press polished sheet vinyl, while still retaining the benefits of roll glass convenience.

- K432 is a soft hand similar to roll-a-glass in stiffness.



Part No.	Gauge Thickness: mm/in		Roll Width: mm/in		Roll Length: m/yd	
K432	0.76	0.030	1370	54	17.8	19.5
 K434	1.02	0.040	1370	54	17.8	19.5

## DIAX-Clear Window Material

- Black polyester DIAX laminated with 4 mil optically clear film.
- Low stretch, high tear strength.
- Ideal for laminate and woven race sail windows.



Part No.	Film: mil	Total DPI: Warp x Fill
F6002X00M	4	2 x 2 840 Black Polyester

## SPF-uv™ Sun Protective Film

This clear UV resistant film with adhesive backing blocks virtually all damaging UV radiation. For application on roller furling genoas or to protect other materials from effects of UV rays.

Application recommendations:

- Use on a clean surface - dirt and salt will prevent an adequate bond.
- Stretch sail to be flat and free of wrinkles.
- Apply SPF-uv in sections (do not attempt one piece head to clew or tack to clew.)
- Keep minimum tension on SPF-uv to keep it flat but not distorted.
- Allow sufficient time for maximum bonding after applying SPF-uv.
- Roll sail with film to the outside roll.
- Check parts of the mast and rigging that could chafe sail.

Part No.	Width: mm/in		Weight: gm/oz		Film: mil
J822	508	20	81	1.9	0.5
J832	762	30	81	1.9	0.5
J862	1524	60	81	54	0.5

## Monofilm

- See-through polyester film for a light weight performance material for boardsails and telltale windows.
- Use J080 series seaming tapes for sewing panels together.

Part No.	Thickness: mm/in		Roll Width: mm/in		Roll Length: m/yd		Weight: gm/oz	
E078	0.12	0.005	1370	54	46	50	111	3.9
E088	0.18	0.007	1370	54	46	50	156	5.5
E080	0.25	0.010	1370	54	46	50	224	7.9



## Adhesive Backed Polyester Monofilm

- Repair clear film products.
- Pressure sensitive adhesive.
- Roll length: 45 metres / 50 yards.



Part No.	Width: mm/in	
J874	1370	54
J872	50	2

## Telltale Windows

- Pre-cut Telltale Windows cut from E201 best quality material.
- Sold in full packs of 10 only.

Part No.	Diameter: mm/in		Thickness: mm/in	
E210	225	8 7/8	0.5	0.02

## Melinex

- Clear polyester film for board sails.

Part No.	Thickness: mm/in		Roll Width: mm/in		Roll Length: m/yd	
E207	0.175	0.007	1524	60	40	43.7
E2075	0.175	0.007	1524	60	5	5.5